



NS006

**Non-Sparking Metric Double Open
Ended Wrenches Aluminium
Bronze**



PRODUCT DETAILS

- Made of aluminium bronze
- 15° head angle
- Open end wrench for tightening of two different sizes of nuts and bolts
- Fulfils product standard DIN 895
- Non-sparking (NS) tools designed for use in potentially explosive environments, where 'traditional' steel tools may create spark
- 15° head angle for optimum access
- To obtain more information about the usage restrictions of non-sparking materials, please refer to the corresponding certificates



Follow the Fish!



PRODUCT ATTRIBUTES

Product		L	b1	b2	a	
NS006-0607	6x7 mm	92 mm	15.5 mm	17.5 mm	5 mm	22 g
NS006-0608	6x8 mm	92 mm	15.5 mm	17.5 mm	5 mm	22 g
NS006-0708	7x8 mm	95 mm	18 mm	22 mm	6 mm	22 g
NS006-0709	7x9 mm	96 mm	18 mm	22 mm	5 mm	25 g
NS006-0809	8x9 mm	105 mm	20 mm	23 mm	6 mm	38 g
NS006-0810	8x10 mm	100 mm	20 mm	23 mm	6 mm	31 g
NS006-0910	9x10 mm	110 mm	21 mm	25 mm	6.3 mm	38 g
NS006-0911	9x11 mm	110 mm	22 mm	26 mm	7 mm	45 g
NS006-1011	10x11 mm	115 mm	23.5 mm	26 mm	7 mm	47 g
NS006-1012	10x12 mm	120 mm	23 mm	28 mm	7 mm	55 g
NS006-1013	10x13 mm	122 mm	24 mm	28 mm	7 mm	60 g
NS006-1014	10x14 mm	124 mm	24 mm	31 mm	7 mm	62 g
NS006-1113	11x13 mm	125 mm	28 mm	29.5 mm	7 mm	65 g
NS006-1114	11x14 mm	125 mm	28 mm	31 mm	7 mm	65 g
NS006-1213	12x13 mm	128 mm	28 mm	28.5 mm	7 mm	67 g
NS006-1214	12x14 mm	130 mm	28 mm	31 mm	7 mm	69 g
NS006-1315	13x15 mm	135 mm	30 mm	33 mm	8 mm	100 g
NS006-1415	14x15 mm	143 mm	31 mm	33 mm	8 mm	90 g
NS006-1416	14x16 mm	143 mm	31 mm	37 mm	8 mm	105 g
NS006-1417	14x17 mm	150 mm	31 mm	37 mm	8.5 mm	120 g
NS006-1617	16x17 mm	157 mm	35 mm	37 mm	8.1 mm	100 g
NS006-1618	16x18 mm	163 mm	35 mm	39 mm	8.3 mm	120 g
NS006-1719	17x19 mm	170 mm	37 mm	41 mm	8.5 mm	135 g
NS006-1722	17x22 mm	175 mm	37.5 mm	45 mm	8.7 mm	150 g
NS006-1819	18x19 mm	179 mm	39 mm	42 mm	9 mm	180 g
NS006-1820	18x20 mm	182 mm	39 mm	49 mm	10 mm	160 g
NS006-1920	19x20 mm	182 mm	41.5 mm	44 mm	10 mm	190 g
NS006-1922	19x22 mm	185 mm	42 mm	47 mm	10 mm	200 g
NS006-1924	19x24 mm	190 mm	42 mm	50 mm	9.6 mm	190 g
NS006-2022	20x22 mm	195 mm	43 mm	46 mm	10 mm	210 g
NS006-2122	21x22 mm	195 mm	44 mm	48 mm	10 mm	225 g
NS006-2123	21x23 mm	200 mm	44 mm	48 mm	10 mm	220 g
NS006-2223	22x23 mm	205 mm	46 mm	50 mm	10.2 mm	250 g
NS006-2224	22x24 mm	210 mm	46 mm	49 mm	10.2 mm	260 g
NS006-2227	22x27 mm	215 mm	46 mm	55 mm	11 mm	270 g
NS006-2326	23x26 mm	220 mm	48 mm	53 mm	11 mm	270 g
NS006-2425	24x25 mm	225 mm	50 mm	56 mm	12 mm	305 g
NS006-2426	24x26 mm	225 mm	50 mm	56 mm	12 mm	305 g
NS006-2427	24x27 mm	230 mm	49 mm	55 mm	12 mm	310 g
NS006-2430	24x30 mm	235 mm	49 mm	61 mm	12 mm	340 g
NS006-2528	25x28 mm	236 mm	53 mm	59 mm	12 mm	390 g
NS006-2629	26x29 mm	245 mm	55 mm	62 mm	12.7 mm	440 g
NS006-2729	27x29 mm	245 mm	55 mm	62 mm	13 mm	430 g
NS006-2730	27x30 mm	250 mm	55 mm	62 mm	12.7 mm	430 g
NS006-2732	27x32 mm	255 mm	54 mm	65 mm	12.3 mm	430 g
NS006-2830	28x30 mm	260 mm	56 mm	62 mm	12.7 mm	450 g
NS006-3031	30x31 mm	260 mm	61 mm	65 mm	14 mm	540 g
NS006-3032	30x32 mm	265 mm	62 mm	66 mm	13.7 mm	510 g
NS006-3034	30x34 mm	265 mm	66 mm	75 mm	15 mm	690 g
NS006-3036	30x36 mm	270 mm	66 mm	75 mm	15 mm	680 g
NS006-3234	32x34 mm	270 mm	66 mm	75 mm	15 mm	730 g
NS006-3235	32x35 mm	285 mm	70.5 mm	75 mm	16 mm	765 g
NS006-3236	32x36 mm	300 mm	70.5 mm	75 mm	16 mm	830 g
NS006-3335	33x35 mm	300 mm	70.5 mm	75 mm	16 mm	840 g
NS006-3436	34x36 mm	300 mm	70.5 mm	75 mm	17 mm	830 g
NS006-3536	35x36 mm	315 mm	70.5 mm	75 mm	16 mm	1000 g
NS006-3638	36x38 mm	330 mm	80 mm	83.5 mm	17 mm	1150 g
NS006-3641	36x41 mm	330 mm	79.7 mm	83.7 mm	18 mm	1210 g
NS006-3642	38x42 mm	340 mm	79.7 mm	83.7 mm	17 mm	1300 g
NS006-4146	41x46 mm	355 mm	83 mm	95 mm	19 mm	1430 g
NS006-4650	46x50 mm	370 mm	93 mm	102 mm	18.5 mm	1640 g
NS006-5052	50x52 mm	380 mm	101 mm	101 mm	19 mm	1900 g
NS006-5055	50x55 mm	385 mm	101 mm	111 mm	20 mm	1950 g
NS006-5060	50x60 mm	400 mm	101 mm	121 mm	21 mm	2275 g
NS006-5062	50x62 mm	405 mm	101 mm	121 mm	21 mm	2300 g
NS006-5560	55x60 mm	415 mm	111 mm	121 mm	21.5 mm	2450 g
NS006-6065	60x65 mm	435 mm	121 mm	131 mm	23 mm	3600 g
NS006-6570	65x70 mm	450 mm	131 mm	141 mm	25 mm	3600 g

Follow the Fish!



Contact: info@bahco.com / www.bahco.com